

EFFICACY OF 3 PROTECTIVE CLOTHING IN VERY SEVERE **HOT** ENVIRONMENT

Michel Aptel* and Victor Candas**

* UAPE - INRS - Avenue de Bourgogne - BP27 - 54500 Vandœuvre - France

** LPPE - CNRS/INRS - 21 Rue Becquerel - 67087 Strasbourg - France

INTRODUCTION

The number of workers exposed to hot environments and the severity of the heat **stress** have decreased in the last decade. Nevertheless, there are still particular situations where workers have to be **exposed** to hot environments [1]. It is the case **for** workers in paper-mill industry where they have to work few hours a week, in a very severe hot environment wearing Ventilated Protective Clothing (VPC). The purpose of the present study was to evaluate the efficacy of 3 VPCs (MARS of VTN®, MSA®, MATISEC®) in a situation involving **75°C** dry bulb temperature and 60°C wet bulb temperature. MARS of VTNB and MSA® VPC have a vortex system to cool the input air and MATISECB have not.

METHOD

The subjects were 3 workers of the paper-mill : their age was respectively subject 1 = 38 ; subject 2 = 24 ; subject 3 = 37 years old. The subjects had never worn any of the 3 VPCs prior to their participation in the study. Each subjects tested the 3 VPCs. The efficacy of the 3 VPCs was **assessed from** the **responses of** heart rate (HR) and rectal temperature (Tre). Measurements were taken before, during and after the exposure. Before the experiments subjects performed a submaximal exercise on a cycle ergometer, for determination of their physical

fitness (indirect $\dot{V}O_{2max}$ evaluation). The following values were found for the 3 subjects respectively : subject 1 = 53, subject 2 = 74 and subject 3 = 36 mlO₂/min.kg. Nine experiments (3 subjects x 3 VPCs) were carried out and maximal duration of exposure never exceeded 30 minutes because the duration of exposure in actual working situation is always lower than 20 minutes. In the hot environment, the subjects remained standing without moving or working. **Thus**, metabolism was low, estimated close to 70 W/m².

As Tre and HR were not stable during the exposure time in hot environment, 2 regressions lines were calculated between each of these two variables and time for each experiment.

In this study the Threshold Limit Values (TLV) for the workers exposed to heat were also determined :

- TLV.HR : $0.75 \times (220 - \text{age})$ b/min [3] respectively subject 1 = 137, subject 2 = 147, subject 3 = 137 b/min
- TLV.Tre : 38.0 °C [4].

In addition to the fact that the subjects were **free** to withdraw **from** the experiment **at** any time, the continuous recordings of HR and Tre were used by the experimenter for imposing the cessation of exposure.

The design is too **small** for statistical analysis, so ~~that~~ only impressions **are** obtained.

RESULTS

Table 1 indicates the exposure time, and the changes in HR and Tre (= slope of the regressions lines) during exposure for each subject in each of the 3 conditions. Three experiments were stopped because HR value had exceeded the fixed TLV for a certain duration of time. **From** the results, it appears that the highest average Tre increase was found under MATISECB condition (1.35°C per hour **for** Tre) associated With the larger average heart-rate (HR) rise with time (2.6 b/min²). The VTN® ensemble allowed some reduction of **this** physiological cost (1.0°C/h of Tre *drift* and 14 b/min² for HR drift). The efficacy of MSA® appeared very good since both Tre and HR were minimal (0.3°C/h and 0.5 b/min² respectively).

Table 1 also indicates the Duration Limit for Exposure (**DLE**), which was derived for each subject in each condition. **DLEs** were determined by assuming a constant rate of change of HR and Tre, and estimating the time required to attain DLE for HR (**DLE HR**) and Tre (**DLE Tre**).

Type of clothing	Subject	Elapsed time, min	dHR/dt b/min ²	$dTre/dt$ °C/h	DLE HR min	DLE Tre min
VTN®	1	26	1.8	1.5	18	51
	2	30	1.1	1.0	51	60
	3	30	1.2	0.4	23	114
MSA®	1	30	0.6	0.6	73	103
	2	30	0.4	0.1	120	109
	3	30	0.4	0.2	35	106
MATISEC®	1	23	2.8	1.7	19	33
	2	30	1.1	1.1	49	63
	3	15	3.7	1.2	1	54

Table 1 : Durations of exposure, slopes of HR and Tre during heat exposure and DLE for each experiment

Type of clothing	VTN®	MSA®	MATISEC®	Mean
Subject	%	%	%	%
1	68	27	71	55
2	36	21	31	33
3	61	43	18	63