

# TOWARD EXPOSURE LIMITS TO LOW FREQUENCY UNDERWATER SOUND: METHODOLOGICAL CONSIDERATIONS FOR HUMAN TESTING

D. Fothergill<sup>1</sup>, J. Sims<sup>1</sup>, M. Curley<sup>1</sup>, E. Cudahy<sup>1</sup>, R. Sylvester<sup>1</sup>, S. Stevenson<sup>2</sup>,  
H. Lynch<sup>2</sup>, R. Arrieta<sup>2</sup>, J. Schmit<sup>2</sup>, D. Sample<sup>2</sup> and M. Pestorius<sup>3</sup>

<sup>1</sup>Naval Submarine Medical Research Laboratory, Groton, CT, USA,

<sup>2</sup>Space and Naval Warfare Systems Center, San Diego, CA, USA,

<sup>3</sup>Applied Research Laboratories, The University of Texas at Austin,  
Austin, TX, USA



## INTRODUCTION

Low frequency underwater sound (LFS) is a concern in the marine environment because of its long propagation distances, its contribution to sound pollution and its potential for adverse biological effects. There are multiple sources of LFS: supertankers, military sonar, oceanographic research systems, oil exploration, drilling platforms, underwater construction and blasting, earthquakes, as well as whale songs. As part of an environmental impact statement for low frequency active sonar, the U.S. Navy is conducting studies investigating the effects of LFS on marine mammals and human divers. The goal of these studies is to determine the limits for acceptable exposures to low frequency active sonar.

The preliminary U.S. Navy human exposure guidelines for LFS (**160-320** Hz) state that exposures should not exceed **160 dB re. 1  $\mu$ Pa (1)**. The cumulative sound exposure duration should not exceed 15 min over a 24-hour period **and** a continuous exposure should not exceed 100 s with a duty cycle no greater than 50%. Currently there is no restriction on dive depth during the sound exposure. A limited number of studies performed on military-trained divers suggest that no physical damage occurs within the exposure guidelines (**2,3**). However, when approaching the upper boundaries of the guidance, military divers tended to approach their limit of subjective tolerance to LFS (**2,4**). Since all previous studies were performed on a highly selected population of well-trained, healthy military divers, the preliminary guidance needs to be adapted for the recreational diving population. In particular, the guidance should account for the possible psychological reactions that may occur following an unexpected LFS exposure in a recreational diver. Such an exposure might startle the diver and result in an inappropriate, rapid ascent to the surface. **An** uncontrolled ascent increases the likelihood of arterial gas embolism (AGE), pulmonary over-inflation syndrome, decompression illness (DCI) and drowning (**5**). We are currently investigating the psychological effects of LFS in recreational divers. This paper addresses some of the methodological issues involved in conducting underwater sound exposures on divers to ensure subject safety and data integrity **and** reliability.

## Sound Variables

The transmission of sound in water is largely unimpeded by the human body since most tissues have the same density as sea water. However, when LFS travels through air-filled body cavities (e.g., lung, sinus and bowel) the change in impedance between body tissues and the air cavities increases the influence of sound on these bodily structures. Listed below are the primary variables required to define underwater sound exposures and their influence on physiological and psychological reactions.

**Sound Pressure Level (SPL).** The pressure of underwater sound is usually expressed in decibels (dB) referenced to  $1 \mu\text{Pa}$ . To compare SPL measured in air (normally referenced to  $20 \mu\text{Pa}$ ) with that measured in water, it is necessary to add **26 dB** ( $20 \log 20$ ) to the  $20 \mu\text{Pa}$  referenced value. Regardless of frequency, experiments in humans and animals, as well as theoretical models, suggest that damage thresholds for sensitive organs (e.g., lung, bowel) occur above **190 dB** (6). Temporary threshold shifts in hearing have been demonstrated at 170 dB (7).

**Frequency.** LFS includes frequencies below 1 kHz, which coincides with the resonant frequencies of various organ systems (e.g., lung, Pacinian corpuscle, bowel) (6). Frequency impacts the perception of vibration (8) and loudness (9).

**Signal type.** There are many signal types (e.g., pure tones, sweeps, warbles). Some signal types such as complex tones produce audible beats at lower frequencies than the constituent pure tones. Depending on their bandwidth and pulse repetition frequency, sweep tones increase the likelihood of matching the resonant frequency of a body structure. Our findings suggest that 7 second hyperbolic sweeps (30 Hz bandwidth) result in similar psychological aversion to pure tones of the same duration (8).

**Duration.** Short sound durations at high SPLs are important for damage thresholds of gas-filled voids (6). Mathematical models of bubble growth implicate long sound durations at high SPLs in the generation of rectified diffusion in supersaturated tissue, theoretically increasing the risk of DCI (10). Long sound durations, even at low SPLs, can cause damage to certain organs such as the ear (7). Duration is also important for subjective tolerance limits (1).

**Near vs. far field.** To simulate the acoustic conditions in the ocean environment, the diver should be placed in the far field so that the acoustic wavefront will be uniform over the diver's body. For LFS, the far field can be defined as beginning at a distance from the sound source equal to twice the maximum dimension of the projecting transducer. Any distances closer than the above calculation is defined as the near field.

**Duty cycle.** It is defined as the percentage of time that sound is present in a repeating interval (e.g., if a 30-s sound repeats after a 30-s pause, then the duty cycle is 50%). We are unaware of studies that have investigated the effects of duty cycle on physiological responses and psychological reactions to LFS.

## Dive Site Selection for Low Frequency Sound Experiments

The choice of dive site used for conducting LFS experiments has considerable implications for data fidelity. An ideal dive site should have a well-con-

trolled environment with easy dive access, anechoic properties and minimal background noise. To avoid any unwanted masking effects on physiological parameters, background noise should be at least 20 dB below the SPL of the frequency of interest. Sources of background noise in artificial pools that should be minimized include pool pumps, nearby vehicle traffic or construction work and 60 Hz power line hum. To obtain uniform SPLs at the diver, it is important to minimize the effects of standing waves that cause spatial deviations in SPL over the sound field. Standing waves are created when sound reflects from surfaces such as pool walls, the bottom and the air-water interface. Most pools and tanks are reverberant environments that preclude their use in LFS experiments. However, there are specially designed anechoic underwater sound testing facilities (e.g., TRANSDEC; Point Loma, CA) that have contoured sides and sound traps that simulate an infinite expanse of water. While deep blue water dive sites provide better anechoic conditions than most artificial pools, their main disadvantages are loss of a controlled environment and an increased complexity of scientific and dive support. Furthermore, open water LFS studies require calculating the transmission loss of sound to ensure that sound beyond the dive site does not have significant impact on the environment.

### **Diver Safety**

The choice of dive depth for experiments on LFS needs to balance issues of sound field integrity (as stated above) and diver safety. When conducting LFS experiments with divers of varying experience, we have found that a dive depth of 1 m maximizes diver safety. At this depth the spatial deviation in SPL over the diver's body is less than 1.3 dB for frequencies between 100 and 500 Hz (8). Suspending a diver at a depth of 1 m essentially eliminates the possibility of barotrauma and DCI caused by an uncontrolled ascent. If dives exceed a 1-m depth, a medical recompression chamber should be immediately available for treatment of AGE or DCI. To prevent uncontrolled ascents caused by reactions to the sound, divers should be provided with a means for immediate termination of the sound exposures upon reaching thresholds of pain or tolerance. Voltage cut-off circuits can also be used for automatically shutting off the power to the sound transducer should SPLs exceed predetermined limits.

Electrical safety is a significant concern when conducting diving experiments, particularly when using high-power underwater sound transducers that may introduce current leakage into the surrounding water. Means for ameliorating the danger of electrocution include using surge protectors and current leakage cut-off switches, isolating the source transducer and grounding electrical equipment to eliminate ground loops.

### **CONCLUSIONS**

The acoustical parameters of LFS might independently affect physiological and psychological responses and must be clearly defined. Obtaining valid scientific data for development of LFS exposure limits requires understanding the impact of the dive site on the sound field. Suggestions for ensuring subject safety

are provided that take into account the inherent risk of the diving environment, as well as, the potential aversive nature and possible physiological effects of LFS.

## REFERENCES

1. Commanding Officer, NSMRL, 1995, Letter, Interim Guidance for Operation of Low Frequency Underwater Sound Sources.
2. Parvin, S.J., Nedwell, J.R., Needham, K., Turnpenny, A.W.H., Thomas, A.J. and Searle, S.L. 1994, The effects of low frequency sonar transmissions on divers and ichthyofauna: Hyperbaric and open water diver studies and the noise exposure of species of fish, Report #DRA/AWL/CR941010/V1.0, Defence Research Agency, United Kingdom.
3. Steevens, C.C., Sylvester, R. and Clark, J. 1997, Effects of low-frequency water-borne sound on divers: open water trial, NSMRL Technical Report 1208, Naval Submarine Medical Research Laboratory, Groton, CT.
4. Russell, K.L. and Knafelc, M.E. 1995, Low frequency water-borne sound manned diving series, Report 10-95, NEDU, Panama City, FL.
5. *U.S. Navy Diving Manual*, NAVSEA, Revision 3, 15 February 1993.
6. Cudahy, E. and Sims, J.R. 1998, Non-hearing physiological effects of sound in the marine environment, in R. Gisiner, et al., (eds.) *Effects of Anthropogenic Noise on the Marine Environment*, Bethesda, MD: Office of Naval Research Workshop, Feb 10-12, 1998.
7. Smith, P.F., Wojtowicz, J. and Carpenter, S. 1988, Temporary auditory-threshold shifts induced by ten-minute exposures to continuous tones in water, Technical Report 1122, NSMRL, Groton, CT.
8. Fothergill, D.M., Sims, J.R. and Curley, M.D. 1998, Diver aversion to low frequency sound, *Undersea and Hyperbaric Medicine*, **25(Suppl)**, 38-39.
9. Cudahy, E., Hanson, E., Sylvester, R. and Stepke, B. 1998, Loudness and annoyance in the presence of underwater sound, *Undersea and Hyperbaric Medicine*, **25(Suppl)**, 39.
10. Crum, L.A. and Mao, Y.I. 1996, Acoustically enhanced bubble growth at low frequencies and its implications for human diver and marine mammal safety, *Journal of the Acoustical Society of America*, **99(5)**, 2898-2907-907.

## ACKNOWLEDGMENTS

Supported by the Chief of Naval Operations N-874. Views expressed in this report are the authors and do not reflect official policy or position of the Department of the Navy, DoD, or U.S. Government.